

Permanent Split Capacitor Commercial Condenser Fan

Open Drip-Proof & Totally Enclosed, Air Over

APPLICATIONS:

For use on condenser cooling fans in commercial air conditioning applications.

FEATURES:

- Capacitor and Outlet Box Included, unless noted
- Reversible Rotation
- Double-Sealed Ball Bearings
- Continuous Duty, Air Over
- Automatic Reset Thermal Overload Protector
- 60°C Ambient
- Dual Voltage
- Class B Insulation




Figure A




Figure B

5.6" Diameter, All Angle Mounting, Hub Ring Mount (2 1/4") (Fig. A)

HP	RPM/ Spds.	Voltage	Catalog Number	Mounting	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wt.
1/3	1075	208-230/460	6727*	Hub	5	2.4/1.2	5	5.9	5.3	11.4	N/A	17
1/2	1075	208-230/460	7475*	Hub	10	2.8/1.4	5	6.4	5.8	11.9	N/A	20
	1075	208-230/460	2201*	Hub	10	3.2/1.6	5	7.4	6.8	12.8	N/A	20
	1075	208-230	8868	Stud	10	3.8	3.0	-	6.3	9.3	.63	21
	1075/1	575	1177	3 Lug	7.5	1.9	3.0	-	-	8.8	-	18.2
3/4	1075	208-230/460	2202*	Hub	12.5	4.8/2.3	5	8.4	7.8	13.8	N/A	23
	1075	208-230/460	6603	Hub	7.5	5.0/2.5	5	6.9	6.3	12.4	N/A	22
	1075	208-230/460	5489	Hub	7.5	5.0/2.5	5	6.9	6.3	12.3	N/A	22
	1075	460	8233	Band	15.0	2.3	3	6.6	6.0	10.2	N/A	19
	1075/1	208-230/460	1254	Band	15	4.6	3.5	-	-	9.8	-	23
1	1080	460	8055	Band	15.0	2.5	5.0	-	6.6	11.6	N/A	20
	1075/1	575	1173	Band	25	2.2	6.0	-	-	13.0	-	26.5

QU = Quantum Precision®

6.3" Diameter, All Angle Mounting, Hub or Stud Mount (4) (Fig. A with 5/8" shaft)

HP	RPM/ Spds.	Voltage	Catalog Number	Mounting	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wt.
1/2	825	208-230	3568	Band	10.0	3.6	6.0	7.0	6.0	13.4	1.5	25
3/4	1075	208-230	3566	Stud	15.0	3.8	6.0	7.0	6.0	13.4	1.5	26
	825	208-230	3567	Stud	17.5	5.3	6.0	8.2	7.8	14.6	1.5	32
1	1075	208-230	3565	Stud	17.5	5.2	6.0	7.5	6.5	13.9	1.5	30
	1075	208-230/460	2203*	Hub	17.5	5.5-5.4/2.6	6.0	10.4	9.9	16.9	1.5	40
	1075	208-230/460	8431	Stud	12.5	5.8-5.4/2.7	6.0	9.9	9.4	16.4	1.8	41
	850	208-230/460	1271	Hub	-	6.4/3.2	6.0	11.4	10.4	18.4	1.0	45
1-1/2	1075	208-230/460	2204*	Stud	20.0	8.5-7.6/3.8	6.0	10.9	10.3	16.9	1.5	43

6.3" Diameter, Resilient Base (Fig. B)

HP	RPM/ Spds.	Voltage	Catalog Number	Mounting	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wt.
3/4	1075	208-230/460	2193*	Resilient	30.0	4.8/2.5	4.1	8.3	7.8	13.1	--	41
1	1075	208-230/460	2686*	Resilient	17.5	5.1/2.6	5.0	10.5	9.3	15.8	1.5	38
1-1/2	1075	208-230/460	2896*	Resilient	20.0	7.5/3.8	5.0	11.0	9.8	16.3	1.5	47